CRFS | EXTRAORDINARY RF TECHNOLOGY

VDK TELECOMMUNICATIONS

DATA SHEET

RFEYE NODE 100-8

INTELLIGENT WIDEBAND RECEIVER

The RFeye Node 100-8 offers class-leading RF performance and extended instantaneous bandwidth for 24/7 ITU-compliant spectrum monitoring and radio geolocation.

The RFeye Node 100-8 uses the latest superheterodyne receiver technology to provide outstanding quality and performance at a highly competitive price. It is a complete spectrum monitoring and geolocation system designed for remote deployment in distributed networks both indoors and outdoors, including in hostile environments. Packaged in a compact, rugged and a weatherproof housing, it has been optimized for size, weight and power (SWaP) and is simple to connect to power and network.

The Node 100-8 is characterized by outstanding phase noise, noise figure, channel retune time and spurious free dynamic range parameters, well above any other product in its class. It also offers all of the multi-mission capability of the RFeye product range allowing multiple concurrent measurements and geolocations to be performed and multiple users to connect simultaneously from remote locations.



100-8 SPECIFICATIONS

Single channel receiver

Switchable RF inputs	3 x SMA connectors

Frequency

Range	9 kHz to 8 GHz

Noise figures at maximum sensitivity (typical)

9 kHz to 83 MHz	11 dB
83 MHz to 1 GHz	9 dB
1 GHz to 2.9 GHz	8 dB
2.9 GHz to 5.9 GHz	7 dB
5.9 GHz to 8 GHz	9.5 dB

Phase noise at 20kHz offset (typical)

Receiver input at 1 GHz	-126 dBc/Hz
Receiver input at 5 GHz	-121 dBc/Hz
Receiver input at 8 GHz	-120 dBc/Hz

Signal analysis

Instantaneous bandwidth	100 MHz
Tuning resolution	1 Hz

Internal frequency reference

Initial accuracy @20°C	±0.1 ppm typ.
Stability over temperature	±0.3 ppm
Ageing over 1 day	±0.04 ppm

Programmable sweep modes

Sweep speed at 2 MHz RBW	390 GHz/s typ.
Sweep speed at 61 kHz RBW	320 GHz/s typ.
User programmable modes	free run continuous, single timed, user trigger, adaptive
Trigger-on-event modes	user defined masks, actions alarms

Sampling

Resolution	16 bits per channel (I&Q)
Rate	125 MS/s I&Q

Third order intercept points with AGC

≤ 1 GHz	+20 dBm typical
> 1 GHz to ≤ 6 GHz	+15 dBm typical
> 6 GHz to ≤ 8 GHz	+20 dBm typical

Local oscillator

Re-radiation	≤ -90 dBm typical

Frequency references

Selectable	Internal, GPS or external
External input	10 MHz ±10 ppm
GPS holdover *(option)*	Sync Backup Module ± 1.5µs / 8hrs

Processor sub-system

CPU	Intel E3845 quad core

I/O

Network	1 x 1 GigE, with POnE
Universal Serial Bus	1 x USB3.0, 1 x USB2.0
2 x expansion ports configurable as:	2 x SyncLinc with < 10 ns RMS accuracy typical, trigger input, external peripheral control
GPS antenna input	1 x SMA passive or active (3.3 VDC)

Data storage

External flash disk	via USB interfaces

System software

Operating system	Linux
RFeye Node Control Protocol	NCP Server (NCPd)
Node Apps (optional)	Logger, EMP, Detectors

Size, weight and power

Dimensions (w, h, d) (Node only)	200 x 50 x 192 mm (7.9 x 2.0 x 7.6 inches)
Dimensions (w, h, d) (with end plates & heat sinks)	200 x 98 x 395 mm (7.9 x 3.9 x 15.6 inches)
Weight (inc heatsink)	4.2 kg (9.3 lbs)
Weight (inc noses / end plates)	6.6 kg (14.5 lbs)
DC power	12 VDC (limits 10-30V)
Power On Ethernet (POnE)	56 VDC

Power consumption

Typical	35 W
Maximum	45 W

Environmental

Operating temperature	-30 to +55 °C (-22 to 131 °F)
Storage temperature	-40 to +71 °C (-40 to 160°F)
Ingress protection	IP67 (with optional end plates)

Vanderkooij Telecommunicatie B.V.
Pieter Zeemanstraat 3
6603 AV, WIJCHEN
www.vdk-tele.com
+(0)880 513 213

CRFS and RFeye are trademarks or registered trademarks of CRFS Limited. Copyright© 2024 CRFS Limited. All rights reserved. No part of this document may be reproduced or distributed in any manner without the prior written consent of CRFS. The information and statements provided in this document are for informational purposes only and are subject to change without notice.

bsi. ISO 9001:2015 Quality Management
UK Certificate number: FS576625